

MAINTENANCE

- Happiness does not require a floor finish. However, in certain applications a floor finish may be desirable to aid in stain resistance, resistance to abrasion or increase gloss level.
- The single greatest cause of damage to any flooring or floor finish is abrasion from dirt and grit. Wherever possible, use walk off mats at entrances and doorways. Vacuum or sweep the floor often to remove any dirt and grit.
- Every application and every building can present different issues which may require variations in the maintenance procedure. The following are general guidelines, which will cover the majority of applications. If you feel your situation is not covered by these guidelines, please contact LG Floors technical service for advice before beginning your maintenance procedures.

Initial Maintenance

Note: Do not begin wet maintenance for at least 3 days after installation is complete, this is to assure the adhesive has had sufficient time to dry and cure.

Damp mopping is allowed after 12 hours.

Daily Maintenance

Remove surface soil, dirt, sand and grit by vacuuming or dust mopping.

General Maintenance

Use standard Maintenance Industry safety practices and precautions whenever performing maintenance procedures.

- Remove surface soil, dirt, sand and grit by vacuuming or dust mopping.
- Before selecting an Option, determine what the visual expectations are, e.g. Shiny, Medium, or Matte finish.

Option 1 - No Wax & No Buff Methods (Matte Finish)

- *Damp Mop*: Clean floor with a neutral pH detergent such as Johnson Diversey 'Stride'.

Follow manufacturer's directions for mixing and using.

And/Or

- *Machine (Auto Scrubber)*: If desired, scrub with a rotary scrubber using a 3M red type scrubbing pad or automatic scrubber with equivalent scrubbing pads or brushes.

Option 2 - Floor Finish (Shiny or Matte)

- Apply 2-3 coats of high quality floor finish such as Johnson Diversey's 'Carefree' or Taski's 'Vision Matte', or equivalent. Apply with a clean finish mop or finish applicator. Follow finish manufacturer's instructions.

- Allow each coat to dry completely before applying the next coat.

* Spray Buffing in lieu of Option 2 is acceptable and will leave a slight luster on the floor.